



ADOLAC CHEM INDIA
POLYMER DIVISION

B - 405

MODIFIED EPOXY RESIN FOR COATING AND FLOORING

DESCRIPTION :-

EPOXILITE B - 405 is Bisphenol- A liquid epoxy resin modified with hydro-generated solvents. This resin is mild-higher viscosity and it proves advantages while formulating epoxy system. The mild-high viscosity improves the cost effectiveness by increasing the filler loading of a formulation. And also a wide range of curing agents are available to cure this epoxy resin low color, mild-high viscosity modified epoxy resin suitable to at ambient temperature. The cured mass gives high gloss and excellent surface finish suitable for coating and flooring applications. The film withstand variety of chemicals includes acids, alkali, alcohols and hydrocarbon solvents. Excellent low color of the hardener makes it materials of choice for flooring applications.

Advantages :-

- Medium viscosity
- High gloss
- Work at low humidity.
- * Excellent chemical resistance
- * Blushing free

Applications:-

- Chemical resistance flooring And coating.
- Self leveling Floorings.
- Construction adhesive & coatings.
- * Civil engineering applications
- * High solids and solvent free applications.
- * Adhesives.

Specification Data: RESIN B - 405

Properties	Unit	Typical Value
Appearance	Visual	Light Yellow
Color	Gardener	3 max.
Epoxy Equivalent Weight	g/eg	160 - 175
Viscosity @25 ^o C	cPs	18000- 22000

Typical Prosperities :- RESIN B - 405

Properties	Unit	Typical Value
Non – volatile content	---	100%
Density	g/ml	2.80
Epoxide value	---	3.72– 4.22
Flash Point	C ⁰	150
Moisture content	---	0.2%

Typical properties are indicated for information only

Packing :- EPOXILITE B - 405 is packed and delivered in plastic drums, 40 kg per drum as a standard pack. Other pack sizes are available on request.

Storage :- EPOXILITE B - 405 should be stored in original tightly closed container, in dry and cool conditions. When exposed to air the product EPOXILITE B - 405 may absorb moisture which may result in viscosity increase, frothing and white carbonation product deposition. In such case it may affect the appearance of final coating/floor topping. When stored in tightly closed container this product has a storage life of at least one year from the date of manufacturing.

Handling :- Do not mix with epoxy hardener until just prior to use since reacts chemically at room temperature. Avoid contact with skin, eyes etc. Please refer to the MSDS of the product for more instructions on safe storage and handling of EPOXILITE B - 405.

Disclaimer

All recommendations for use of our products whether given by us in writing, verbally or to be implied from the results of tests carried out by us are based on the current state of our knowledge. Although, the information contained in this sheet is accurate, no liability can be accepted in respect of such information. We warrant only that our product will meet the designated specifications and make no other warranty either express or implied, including any warranty of merchantability or fitness for a particular purpose as the conditions of application are beyond our control.

For Additional Information, Please Contact:

ADOLAC CHEM INDIA

101/6 'X' ROAD, SWAMIJI NAGAR, HOWRAH – 711108

E-mail :- adolacchemindia@gmail.com / info.epoxiliteindia@gmail.com